DuraShield Series – Fiberglass Enclosures

Flush Fitting Cover





Applications

Extremely rugged fiberglass enclosure with low profile design and shallow depth. Accommodates direct-to-wall mounting. The flush cover is well suited to wireless communication and operator interfaces.

Construction

- Hot compression molded fiberglass reinforced polyester (thermoset).
- Poured polyurethane seamless gasket provides watertight, rain-tight, environmental seal
- · Submersible, non-corrosive environmental design
- Rounded edges, minimal protrusions or exposed pocket area for accumulation of dust or debris
- 304 stainless steel used on all external hardware
- Flat lift-off cover with four captive screws (M6 x 35mm)
- All bosses utilize threaded brass inserts accepting M6 screws
- · Optional mounting feet available
- 17-22 lb·in cover screw torque
- · Color: Gray

Enclosure Shipping Schedule 1 - 5 days Color indicates shipping lead time in business days.

DU554AW

DuraShield Series Fiberglass Enclosures				
Part Number	Price	Enclosure Overall Size HxWxD		
DU554W	\$41.50	4.72 x 4.80 x 3.58 [120 x 122 x 91]		
DU594W	\$75.00	4.72 x 8.66 x 3.58 [120 x 220 x 91]		
DU774W	\$59.00	6.30 x 6.30 x 3.58 [160 x 160 x 91]		
<i>DU7114W</i>	\$78.00	6.30 x 10.24 x 3.58 [160 x 260 x 91]		
DU10105W	\$99.00	9.84 x 10.04 x 4.76 [250 x 255 x 121]		
DU10165W	\$153.00	9.84 x 15.75 x 4.76 [250 x 400 x 121]		
DU14144W	\$193.00	14.17 x 14.17 x 3.58 [360 x 360 x 91]		
DU16165W	\$207.00	15.94 x 15.75 x 4.76 [405 x 400 x 121]		
DUL24168W	\$318.00	23.63 x 16.54 x 8.44 [600 x 420 x 214]		
Notes: Dimensions in inches [millimeters].				

Mounting Feet for DuraShield Series Enclosures				
Part Number	Price	Fits	Wt (lb)	
DUMTGKIT	\$13.75	up to 16 x 16 x 5in (HxWxD) DuraShield series enclosures	0.14	
DULMTGKIT	\$25.00	18 x 12 x 7in (HxWxD) and larger DuraShield series enclosures	0.2	

Listings

- UL/cUL 50/50E/508, Types 1, 3, 3S, 4X, 6, 6P, 12 [UL File E64358]
- CSA Certified, Types 1, 3, 3S, 4X, 6, 6P, 12 [CSA File LR069014]
- NEMA Ratings 1, 3, 3S, 4X, 6, 6P, 12
- IEC 60529 IP66 [File E362920]
- Flammability Rating: UL94-V0
- · Self-extinguishing non-halogenating, non-flame propagating
- Temperature Range -26°F to 257°F [-32°C to 125°C]
- · Certifications: CSA, UL









tENC-225 **General Purpose Enclosures**

DuraShield Series – Fiberglass Enclosures

Dimensions for DuraShield Series Enclosures





See our website: www.AutomationDirect.com for complete engineering drawings.

tENC-226 General Purpose Enclosures 1 - 8 0 0 - 6 3 3 - 0 4 0 5